

# CPS SCA2~3.6KTL-PS1/EU

## Single-Phase String Inverter

2-3.6kW • 1 MPPT • 500Vdc System



### Efficient

#### Appealing yield

- 1 MPPT with Max. Efficiency 97.3%
- Easily compatible with various PV module based on max. input current 15A per MPPT
- ≥150% DC/AC ratio
- Lower startup & wider MPPT voltage

### Smart

#### Pragmatic option

- Communication interfaces [RS485/Wi-Fi (Standard) & 4G (Optional)]
- Built-in Bluetooth and App for local and remote monitoring
- Support zero export by meter

### Safe

#### Solid quality

- Durable and robust component
- IP65 & C5 protection
- Type II SPD for both DC and AC

Model Name	CPS SCA2KTL-PS1/EU	CPS SCA3KTL-PS1/EU	CPS SCA3.6KTL-PS1/EU
<b>DC Input</b>			
Max. DC Voltage	500Vdc		
MPPT Operating Voltage Range	50-490Vdc		
Start Voltage	70Vdc		
Rated DC Voltage	360Vdc		
Number of MPPT	1		
Number of DC Connection Sets per MPPT	1		
Max. input current per MPPT	15A		
Max. DC short-circuit current per MPPT	20A		
String Fuse	/		
DC Disconnection Type	Integrated Switch		
<b>AC Output</b>			
Rated AC Power	2kW	3kW	3.6kW
Max. AC Power	2.2kVA	3.3kVA	3.6kVA
Rated AC Voltage	220/230V		
AC Voltage Range <sup>1</sup>	160 - 300V		
Grid Connection Type	L/N/PE		
Max. AC Current	10A	15A	16A
Grid Frequency	50/60Hz		
Grid Frequency Range <sup>1</sup>	45-55/55-65Hz		
Power Factor (cosφ)	>0.99(±0.8 adjustable)		
Current THD	< 3%		
AC Disconnection Type	/		
<b>System Data</b>			
Topology	Transformerless		
Max. Efficiency	97.3%	97.3%	97.3%
Euro Efficiency	95.9%	96.3%	96.5%
Consumption at Night	< 1W		
<b>Protection</b>			
DC reverse connection protection	Yes		
AC short circuit protection	Yes		
Leakage current protection	Yes		
Grid monitoring	Yes		
Ground fault monitoring	Yes		
Surge Protection	DC Type II / AC Type II		
AFCI	Option		
<b>Environment Data</b>			
Ingress Protection	IP65		
Cooling Method	Natural Convection		
Operating Temperature	-25°C to +60°C		
Ambient Humidity	0 - 100%		
Altitude	4000m		
<b>Display and Communication</b>			
Display	LED + APP(Bluetooth)		
Communication	RS485/Wi-Fi (Standard) & 4G (Optional)		
<b>Mechanical Data</b>			
Dimensions (W*H*D)	320 * 344 * 137mm		
Weight	6.5kg		
DC Connection Type	MC4 (Max. 6mm <sup>2</sup> )		
AC Connection Type	Plug and play connector		
<b>Safety</b>			
Certifications <sup>2</sup>	EN 61000-6, EN/IEC 62109, IEC 61727, IEC 62116, VDE 4105, CEI 0-21, EN50549-1, VDE0126-1-1, NTS type A, UNE 217002, RD 647, UNE 217001, INMETRO PORTARIA N° 140, AS4777.2		

<sup>1</sup> AC Power is different under different rated AC voltage.

<sup>2</sup> The certificates are for reference only. Please consult the local sales staff for detailed certification.