

CPS SCH275KTL-DO/EU

Chint Power 1500V String Inverter
High Return of the Whole Life Cycle



Low Investment

Three-phase string series inverters products providing standard configuration DC switch, integrated DC combiner box, standard class II lightning protection, optional PLC/RS485 communication, which can match the requirements of different customers.

High Profits

High DC/AC ratio up to 1.5; Three-phase string inverters can provide 99.0% maximum efficiency, 98.5% Euro efficiency, 99.5% MPPT efficiency, advanced topology design and international known device options, which can guarantee the profits of the Whole Life Cycle.

Maintenance Warranty

String inverter can support remote monitoring, fault diagnosis and software upgrade, 7*24H after-sales service can guarantee the maintenance of the Whole Life Cycle.

Model Name	CPS SCH275KTL-DO/EU	CPS SCH275KTL-DO/EU2
DC Input		
Max. DC Voltage	1500Vdc	
MPPT Operating Voltage Range	500-1450Vdc	
Start Voltage/Power	550Vdc / 500W	
Rated DC Voltage	1190Vdc	
Number of MPPT	12	6
Number of DC Connection Sets per MPPT	2	3
Max. DC input current	30A*12	60A*6
Max. DC short-circuit current per MPPT	50A	90A
DC Disconnection Type	Integrated Switch	
AC Output		
Rated AC Power	275kW	
Max. AC Power	275kVA	
Rated AC Voltage	800V	
Rated AC Voltage Range	680 - 880Vac	
Grid Connection Type	3Φ / PE	
Max. AC Current	198.5A	
Grid Frequency	50/60Hz	
Grid Frequency Range	47-53/57-63Hz	
Power Factor (cosφ)	±0.8 (adjustable)	
Current THD	< 3%	
AC Disconnection Type	-	
System Data		
Topology	Transformerless	
Max. Efficiency	99.0%	
Euro Efficiency	98.5%	
Consumption at Standby/Night	<30W / <6W	
Protection		
DC reverse connection protection	Yes	
AC short circuit protection	Yes	
Leakage current protection	Yes	
Grid monitoring	Yes	
Ground fault monitoring	Yes	
Surge Protection	DC Type II / AC Type II	
Environment Data		
Ingress Protection	IP66	
Cooling Method	Cooling Fans	
Operating Temperature	-30°C - +60°C	
Ambient Humidity	0 - 100%	
Altitude	4000m	
Display and Communication		
Display	LED+ APP	
Communication	RS485(Standard) / PLC(Optional)	
Mechanical Data		
Dimensions (W*H*D)	1100 * 680 * 337mm	
Weight	105kg	
DC Connection Type	MC4	
AC Connection Type	OT/DT Terminal	
Safety		
Certifications	IEC/EN 61000-6, IEC/EN 62109, IEC 61727/62116/60068/61683, EN 50530, NBR 16149/16150	

* "Output Voltage Range" and "Output Frequency Range" may be differ according to specific grid codes.